

Cutting-off wheel INOX

A 960 TZ SPECIAL



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■■■■
Aggression	■■■■■■■□
Service life	■■■■■■■■

Product benefit

Free of iron, sulphur and chlorine - Short cutting times and long service life - Low thermal load - Low burr formation - Optimized bonding for considerably longer service life - For diverse applications - 25 pieces delivered in the Kronenflex® box for long lasting high performance and moisture protection|Free of iron, sulphur and chlorine - Short cutting times and long service life - Low thermal load - Low burr formation - Optimized bonding for considerably longer service life - For diverse applications

Application

Stainless steel	●
Steel	●

Target group

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop
- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Width x Bore in mm	Form	Max. operating speed	Max. RPM	Packing unit/pcs.	Cat. number
105 x 1 x 16	— —	80 m/s	14500 rpm	25	326432
115 x 1 x 22,23	— —	80 m/s	13300 rpm	25	322180
125 x 1 x 22,23	— —	80 m/s	12200 rpm	25	322181

Klingspor Schleifsysteme GmbH und Co. KG
 Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de

